

GRAND RAIL



Construction

- Wind resistance of the tent when opened: 120km/hr
- Reinforced upper and lower hull with stainless steel fittings
- ★ Luggage rack integrated into hull with loading lockers and 6 x anchor points. Loading capacity: 20kg
- · Gas strut easy opening and closing mechanism
- 4 x adjustable safety catches to secure closed
- 2 x built-in aluminium rails to attach the hull onto the roof racks
- 6 x mounting brackets for attaching to roof bars
- Fabric secured to hulls by cable fitted into recessed groove
- 2 x fixing points for the ladder on each side of the hull
- 1 x aluminium ladder (and storage cover), with sliding action to follow vehicle movement
- 1 x removable and rechargeable LED torch

Ventilation

- Ventilation fan
- Capacity 11.6m3/minute
- Automatic and silent operation
- Vent powered by an integrated solar panel, giving 24 hours battery life between charges
- Draws away accumulated heat and avoids condensation build up

Fabric

- High quality double stitched, aluminised polyester fabric. (6 x ISO ratings)
- Tear resistant mosquito mesh
- Stitched-in elastic drawstring around the tent retracts the fabric when stowing
- 6 x fabric coatings; reflects the sun rays, anti UV, non perishable, 100% waterproof and breathable
- High density foam mattress with zipped cover (3 x ISO ratings)
- Back door and front window with mosquito mesh, zipper and Velcro fastening, integrated window
- 2 x side doors with mosquito mesh, double sided zipper and Velcro fastening
- Storage pockets and fixed ceiling storage net



Options

- Colour of hull: White or Black
- Thermal insulation, gain up to 6º in winter conditions

Guarantee

- 5 years guarantee on fabric, hull and mechanism
- 2 years guarantee on Gelcoat, accessories and ventilation system
- Traceability with the serial number

	Test Mode
100% Polyester	
Acrylic	
164cmx243cm	ISO 22198
240g/m²	ISO 3801
	ISO 19394-1
140 daN	
100 daN	
	ISO 13937-1
2.0 daN	
2.0 daN	
85cm	ISO 811
6 sides coated	ISO 105 b04
	Acrylic 164cmx243cm 240g/m² 140 daN 100 daN 2.0 daN 2.0 daN 85cm

MATTRESS quality		Test Mode
Density	28kg/m³	ISO 845
Traction resistance	155 kPa	ISO 1798
Air permeability	828L / dm²	ISO 9237

Distributed in your region by:

